SAFETY DATA SHEET

CB60 H



Section 1. Identification of the material and the supplier

Product: CB60 H

Product Item: SC, SA, ST series - Silicone coated glass filament fabric,

silicone coated texturized glass fabric, silicone coated silica

fabric

PC PA PT series - PU coated glass filament fabric, PU coated

texturized glass fabric, PU coated silica fabric.

Restriction of Use: Refer to Section 15

New Zealand Supplier: RYANFIRE Products

Address: 11 Ashfield Road

Wairau Valley Auckland, 0627

Telephone: +64 9 443 0362

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 9 August 2024 v1.1

Section 2. Hazards Identification

This substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2020.

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Fiberglass	To 100	65997-17-3
Polyurethane/Silicon rubber		

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes If eyes become irritated, flush immediately with lukewarm water for 15

minutes. Seek medical assistance if needed.

If on Skin
If skin becomes irritated, do not rub or scratch. Wash the affected area

with soap and water. Seek medical assistance if needed.

If Swallowed Not considered a route of exposure.

If Inhaled Remove from further exposure. If Cough or other symptoms develop, seek

medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: Ingestion of this product is unlikely. However ingestion may produce

gastro-intestinal irritation and disturbances.

Inhalation: Mechanical irritation of the mouth, nose and throat.

Skin: Exposure to this product may cause temporary irritation to the skin.

Itching and possible inflammation are a mechanical reaction to the fibers

and are not damaging in the way that chemical irritants may be.

Product Name: CB60 H
Date of SDS: 9 August 2024

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Page 1

Eye: Dust from this product may cause temporary mechanical irritation to the

eves.

Chronic: Chronic respiratory or skin conditions will not improve and may worsen

with exposure to this product.

Section 5. Fire Fighting Measures

Hazard Type	Non-Flammable/Non-Combustible
Hazards from combustion products	None known
Suitable Extinguishing media	Dry chemical, foam, carbon dioxide, and water fog.
Precautions for firefighters and special protective clothing	Use normal firefighting procedures.
HAZCHEM CODE	None Allocated

Section 6. Accidental Release Measures

Pick up any large pieces. Use high efficiency vacuum to clean up spilled material. Use wet sweeping where sweeping is necessary. Do not use compressed air for clean-up. Clean-Up Procedures: Collect material and place in a suitable container for disposal as non-hazardous waste. Dispose as per Section 13.

Section 7. Handling and Storage

Precautions for Handling and Storage:

- Handling and use in a manner consistent with good industrial & manufacturing techniques and practices.
- Store in un-opened containers under cool and dry conditions.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

TWA STEL
Substance ppm mg/m³ ppm mg/m³

Particulates Not Otherwise Classified of particles and

Fiberglass (respirable nuisance dust)

10mg/m3 for inhalable 3mg/m3 for respirable

OSHA PEL: 5mg/m3 ACGIH TLV: 10 mg/M3 Other: 3x10(6)/M3

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14TH EDITION.

Engineering Controls

If dust is generated, provide local exhaust ventilation to control airborne levels below ACGIH TLV-TWA exposure. Particular care should be taken when working with material that has been in service to minimize dust. If exposure limits are exceeded or if irritation is experienced, approved respiratory protection should be worn.

Personal Protection Equipment

Product Name: CB60 H SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 9 August 2024 Tel: 64 9 475 5240 www.techcomp.co.nz



Eyes	Wear safety glasses with side shields or goggles when handling this material.
Skin	Use appropriate workplace clothing and procedures when using this material
Respiratory	If airborne dust is present, use a NIOSH approved particulate respirator. (3M 8710) Comments This product contains no known OSHA hazardous ingredients per 29 CFR 1910.1200.

Section 9 Physical and Chemical Properties

_	
Appearance	Flexible cloth
Colour	Black, red, gray, white
Odour	Odourless
Odour Threshold	Not available
pH	Not available
Boiling Point	Not available
Melting Point	300°C
Working Temp	Under 260°C
Freezing Point	Not available
Flash Point	Not available
Flammability	Not available
Upper and Lower	Not available
Explosive Limits	
Vapour Pressure	Not available
Vapour Density	Not available
Density	Not available
Water Solubility	Not available
Partition Coefficient:	Not available
Auto-ignition	Not available
Temperature	
Decomposition	Not available
Temperature	
Kinematic Viscosity	Not available
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous	Not available
reactions	
Conditions to Avoid	Not available
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition	In a fire, product produces small amounts of incompletely
Products	burned Hydrocarbon gases. Carbon monoxide; carbon dioxide

Section 11 Toxicological Information

Direct exposure to fiberglass or exposure to fiberglass dust may irritate the skin, eyes, nose, and throat. Fiberglass may cause itching due to mechanical irritation from the fibers. Breathing fibers may irritate the airway resulting in coughing and a scratchy throat.

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.

Product Name: CB60 H SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 9 August 2024 Tel: 64 9 475 5240 www.techcomp.co.nz

Page 3

Eye	Not applicable.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive	Not applicable.
Toxicity	
Germ Cell	Not applicable.
Mutagenicity	
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method: Dispose of according to local regulations

Precautions or methods to avoid: None known.

Section 14 Transport Information

This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2020

Section 15 Regulatory Information

This substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2020.

Section 16	otner ini	formation
------------	-----------	-----------

1			
Gl	ne	60	147
VI.	\mathbf{v}	30	LL V

Cat Category

EC₅₀ Median effective concentration. EEL Environmental Exposure Limit. EPA Environmental Protection Authority

HSNO Hazardous Substances and New Organisms.

HSW Health and Safety at Work.

LC₅₀ Lethal concentration that will kill 50% of the test organisms

inhaling or ingesting it.

LD₅₀ Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

OSHA American Occupational Safety and Health Administration.

TEL Tolerable Exposure Limit.

TLV Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level
WES Workplace Exposure Limit

References:

Product Name: CB60 H SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 9 August 2024 Tel: 64 9 475 5240 www.techcomp.co.nz

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14th edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2020
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 9 August 2024 Review Date: 9 August 2029

Product Name: CB60 H SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 9 August 2024 Tel: 64 9 475 5240 www.techcomp.co.nz