



## DESCRIPTION

Ryanfire CB60H is a highly flexible, water resistant, and fire rated fabric barrier used in seismic linear gaps. CB60H is ideal for linear seals that require high movement and may be used for gaps up to 160mm wide.

CB60H has a hydrophobic surface and is water resistant making it suitable for temporary exposure to light rain showers during construction.

Ryanfire CB60H will provide up to 60 minutes of fire protection.

## CERTIFICATION

Ryanfire CB60H has been tested and in accordance with AS1530.4:2014 at IANZ/NATA accredited laboratories.

## APPLICATION

CB60H is installed within large seismic linear gaps. Cut the CB60H to size according to the movement required. The CB60H is secured into place with 25mm wide stainless steel flat bar.

For joints, overlap the 2 pieces by 100mm and use 10mm stainless steel staples.

Ryanfire Ryansil may be used to provide an additional water resistant seal along the edges.

## PRODUCT DIMENSIONS


CB60H is available in rolls of 300mm x 10m

Colour: Grey



Ryanfire CB60H

Please contact the technical department for specific and more detailed "V" drawings.



## FEATURES

- Tested to AS1530.4:2014
- Easy installation
- Water resistant seismic seal
- Up to 60mins FRR

The information provided in this document is issued in good faith. As part of Ryanfire Products Ltd ongoing product development and testing, we reserve the right to modify product specifications without notice. Any drawings given are for illustrative purposes only. Ryanfire Products Ltd accepts no liability whatsoever for any loss, damage or injury arising from the misinterpretation or misuse of the information given. Subject to our standard terms and conditions.

For more information please contact Ryanfire  
info@ryanfire.co.nz 09 443 0362