

SAFETY DATA SHEET

Ryanfire TD Fire Collar



Section 1. Identification of the material and the supplier

Product: **Ryanfire TD Fire Collar**
Product Use: Suitable for use around various types of insulation, combustible pipes, cables and Pair coil services.
Restriction of Use: Refer to Section 15

New Zealand Supplier: **RYANFIRE Products Ltd**
Address: 11 Ashfield Road
Wairau Valley
Auckland, 0627

Telephone: +64 9 443 0362
Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 7 March 2024 v2

Section 2. Hazards Identification

This substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2020.

Section 3. Composition / Information on Hazardous Ingredients

Ryanfire TD Fire Collars are a Stainless Steel casing with fixing legs, pre lined with a rubberised graphite loaded strap most commonly fixed around combustible Insulation, cable bundles or combustible pipes.

Ryanfire TD collars are tested on cast concrete substrates of 100mm or more. They are design to be dropped into leave a flush surface.

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Not considered a route of exposure.

If on Skin Wash with plenty of soap and water.

If Swallowed Not considered a route of exposure.

If Inhaled Not considered a route of exposure.

Most important symptoms and effects, both acute and delayed

Symptoms: None known.

Section 5. Fire Fighting Measures

Hazard Type	Non-Flammable/Non-Combustible
Hazards from combustion products	None known
Suitable Extinguishing media	Use media suitable for surrounding materials

Precautions for firefighters and special protective clothing	No special precautions or clothing needed beyond fire BA
HAZCHEM CODE	None Allocated

Section 6. Accidental Release Measures

Sweep up and reuse if possible. If not, dispose of according to Local Regulations.

Section 7. Handling and Storage

Precautions for Handling/Installation and Storage:

- Position TD Collar around the penetrating pipe and push down into the substrate, until the tabs are flush with the surface of the substrate, secure mild steel fixings through each leg of the collar to a minimum embedment of 32mm. Any annular gap filled with Ryanfire Mastic.

Detailed "V Drawings" available on request or Ryanfire website

TD Collar Codes & Dimensions							
Code	TD 40	TD 50	TD 65	TD 80	TD 100	TD 125	TD 160
Nom. Pipe Diameter (mm)	40	50	65	80	100	120	150
Outside	58	68	85	102	136	152	200
Inside Diameter	45	55	65	84	110	125	164
Collar height	130	130	130	130	130	130	130
Core Drill size	72	82	102	112	150	162	225

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³

No ingredients have exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14TH EDITION.

Engineering Controls

No special requirement.

Personal Protection Equipment

Eyes	Not required.
Skin	Not required, but always good practice to wear protective gloves.
Respiratory	Not required.

Section 9 Physical and Chemical Properties

Appearance	Standard sizes from 40mm to 160mm diameter. Oversized collars available on request.
Material	Stainless Steel – rust free.
Colour	Stainless Steel colour

Odour	Not available
Odour Threshold	Not available
pH	Not available
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	Not available
Flammability	Not available
Upper and Lower Explosive Limits	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Density	Not available
Water Solubility	Not available
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Kinematic Viscosity	Not available
Particle Characteristics	Not available
Fire Testing	Tested to AS1530:2014 / AS4072.1-2005 at IANZ accredited fire testing laboratories.
Fire Ratings	30, 60 or 120 minute fire ratings — see Ryanfire website for latest charts.
Other	FPANZ Passive Product Registered. NZ made. Test documentation available on request.

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	Not available
Conditions to Avoid	Not available
Incompatible Materials	Not available
Hazardous Decomposition Products	Not available

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Not applicable.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method: Dispose of according to Local regulations

Precautions or methods to avoid: None known.

Section 14 Transport Information

This product is NOT classified as a Dangerous Good for transport in NZ ; NZS 5433:2020

Section 15 Regulatory Information

This substance is NOT hazardous according to the EPA Hazardous Substances (Classification) Notice 2020.

Section 16 Other Information

Glossary

Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2023 14th edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-

date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 7 March 2024

Review Date: 7 March 2029