

Products: RYANFIRE HP-X
Approval: AS 1530.4/AS 4072.1
BK: 51
Ref: EWFA 56662701
ID: B
Scenario: Penetration seal to cable bundle
Services: Up to 8 optical cables (Ø30mm)
Construction: 116mm FR plasterboard / Masonry wall
Annular: 10-15mm
Max Aperture: Ø50mm
Fire Integrity: 60 minutes
Fire Insulation: 60 minutes

Web based drawings are for example only. Fire performance of any system is dependant on, but not limited to size of opening, substrate, if penetrations are passing through, type, size and number. Please refer to Ryanfire technical department for detailed and specific fire performance information.



Client

Job Title

Drawing Title

**Ryanfire HP-X to cable bundle
116mm plasterboard wall**

Scale

NTS

Date

June 2021

Sheet Size

A3

Drawn By

Drawing Number


V36.8

Rev

1.0

INSTALLATION INSTRUCTIONS

1. ENSURE THE APERTURE IS CLEAN AND FREE OF DUST AND DEBRIS.
2. APPLY RYANFIRE HP-X INTO THE APERTURE AROUND THE CABLES TO THE FULL DEPTH OF THE PLASTERBOARD (13MM)
3. CLEAN ANY EXCESS HP-X USING A DAMP CLOTH.
4. REPEAT THIS PROCESS ON THE OPPOSITE SIDE OF THE WALL.



Please note: Ryanfire Products Ltd owns and has copyright in these drawings. They are to be used only for the purpose for which they were intended and supplied and are not to be sold, transferred or made available for use by a third party.

Any misuse of these drawings will result in legal proceedings.

All errors and omissions excepted - the information contained within this drawing is believed to be correct on the date of publication, and is based upon tested and certified solutions. The policy of **RyanFire Products Ltd** is one of constant improvement. Installers must therefore ensure that they are following the latest published drawings, test evidence and instructions. Whilst **RyanFire Products Ltd** will endeavour to keep its publications up to date, the accuracy of the information contained within this drawing may be affected by pertinent changes in the law or regulatory requirements and alterations or amendments to the specification of the **manufactured** products. Terms and conditions of sale apply.

RYANFIRE Technical Support: info@ryanfire.co.nz - Tel 09 443 0362