150MM CONCRETE **FLOOR** 50MM RYANFIRE HP-X 2 LAYERS RYANROCK 6050 (100MM)

Products:

Ref:

- RYANFIRE HP-X
 - **RYANROCK 6050**
- Approval: AS 1530.4/4072.1 BK:
 - 207 23SFR00007
- ID:
- Scenario: Penetration seal to cable bundle
- Up to Ø100mm cable bundle: Services:

3 x 25mm² mains

- 3 xØ25mm flexi conduits
- TPS, Data
- Annular: 25-35mm
- Construction: 150mm concrete floor
- Fire Integrity: 90 minutes Fire Insulation: 90 minutes

Web based drawings are for example only. Fire performance of any system is dependant on, but not limited to size of opening, substrate, if penetrations are passing through, type, size and number. Please refer to Ryanfire technical department for detailed and specific fire performance information.



RYANFIRE Technical Support: info@ryanfire.co.nz - Tel 09 443 0362

MIXED CABLE BUNDLE

Ryanrock & HP-X to cable bundle

150mm concrete floor Scale

All errors and omissions excepted. The information contained within this drawing is believed to be correct on the date of publication, and is based upon tested and certified solutions. The policy of Ryanfire Products is one of constant improvement. Installers must ensure that they are following the latest published drawings, test evidence and instructions. Whilst Ryanfire Products will endeavour to keep its publications up to date, the accuracy of the information contained within this drawing may be affected by pertinent changes in the law or regulatory requirements and alterations or amendments to the specification of the manufactured products. Terms and conditions of sale apply.

Ryanfire Products owns and has copyright to these drawings. They are to be used only for the purpose for which they were intended and supplied and are not to be sold, transferred or made available for use by a third party. Any misuse of these drawings will result in legal proceedings.

INSTALLATION INSTRUCTIONS

UNDERSIDE OF THE FLOOR.

SURFACE OF THE FLOOR.

DUST AND DEBRIS.

1. ENSURE THE APERTURE IS CLEAN AND FREE OF ANY

INSERT 2 LAYERS OF 50MM THICK RYANROCK 6050

APPLY RYANFIRE HP-X TO A DEPTH OF 50MM INTO THE ANNULAR GAP BETWEEN THE CABLE BUNDLE AND THE CONCRETE FLOOR. ENSURE THE GAP IS COMPLETELY FILLED UNTIL FLUSH WITH THE TOP

REMOVE ANY EXCESS HP-X WITH A DAMP CLOTH.

INTO THE ANNULAR GAP AROUND THE CABLE BUNDLE, WITH THE FIRST LAYER FLUSH TO THE

> July 2024 NTS

Drawing Number

V29.45

3.0